

# RADIUS Server

VCS **RADIUS server** settings can be managed in this information block:

Screenshot: *RADIUS Server settings window*

RADIUS SERVER

Bind to address:	<input type="text"/>	Specify your server IP addresses (separated by comma) to bind to, empty field means bind to all addresses.
	empty - bind to all	
Accounting port:	<input type="text" value="1000"/>	Listen for accounting packets on specified port
Authorization port:	<input type="text" value="1000"/>	Listen for authorization packets on specified port, same for dynamic routing if available
Number of workers:	<input type="text" value="2"/>	Number of threads that process packets. The value of this parameter also affects on numbers of SIP workers.
Max call length:	<input type="text" value="7200"/>	Maximum call duration in seconds, for customers in <b>postpaid</b> mode.
Changes will be only applied after you restart RADIUS server from Task Scheduler section		

Field	Description
<b>Bind to Address</b>	Specify your <b>VCS server IP addresses</b> , separated by a comma, to bind RADIUS to
<b>Accounting Port</b>	Specify the <b>accounting port</b> here. By default, the field value is <b>1813</b>
<b>Authorization Port</b>	Specify the <b>authorization port</b> here. By default, the field value is <b>1812</b>
<b>Number of Workers</b>	Number of <b>RADIUS workers</b> . The value of this parameter also <b>affects SIP workers' number</b> .
<b>Max Call Length</b>	Limit maximum call length in <b>seconds</b>