

# Panel Configuration

## In this article

- [Configuration File](#)
- [Per Reseller Configuration](#)
- [Configuration Options](#)
  - [General Settings](#)
  - [Output Formatting](#)
  - [Date and Time Formatting](#)
  - [Payment Gateways: PayPal](#)
  - [Payment Gateways: Authorize.Net](#)
  - [Section: Charges History & Payments History](#)
  - [Section: Usage History / Detailed](#)
  - [Section: Usage History / Summary](#)
  - [Additional Settings](#)
- [Knowledge Base Articles](#)

## Configuration File

The next step is to tune Client Panel settings. If you are using default deployment, the configuration is located at `/opt/jerasoft/vcs-data/conf/cp-customer-params.json`. If you are moving the panel to the other host, the file should be located in `<YOUR-PATH>/portal-backend/config/customer-params.json`.

During the installation process, the file is pre-created with all general settings like billing credentials, tokens, etc. At the same time there is a set of parameters that can be configured like:

- Payment gateway credentials
- Default locale and output settings
- Date and time formatting options
- Rates and costs rounding

To simplify the process, your deployment provides the `/opt/jerasoft/vcs/portal-backend/config/customer-params.default.json` file. This file has all the available settings with their default values. You do not need to change this file, it is provided as a reference.

## Per Reseller Configuration

The structure of your configuration file allows you to have different settings for different **Resellers** in the system. By default, the file contains a single section called **"default"** with all custom settings. If you want to have multiple Client Panels (for example, separated by domain names), you need to add another section with a simple distinguishable name and put all related settings in this section. The name may consist of Latin characters, numbers, minus and underscore characters.

After that, you need to pass this name from your web-server to the panel using FastCGI parameter called **"CONFIG\_ID"**. It will tell panel which part of config to read to display a related Client Panel. If you are using **nginx** as your web server, use the following statement to pass the parameters:

### Nginx Config

```
fastcgi_param CONFIG_ID "special";
```

Additionally, in the admin panel of the billing system, you'll need to add a **User** for each Reseller in the SystemUsers section. For each such user, set the **API - Client Portal Role**. From settings set up there, you will also get a login, password, and CoreAPI token values for the `customer-params.json` file.

### ⚠ Attention

Please note that for correct work each Reseller has to have its own separate redis databases (**redisMain** and **redisCache** are at db 1 and 2 respectively by default). **Redis** instance supports 16 databases (0-15 in numeric values) by default. You can increase the number of available databases in Redis config if needed.

## Configuration Options

As mentioned above, you can use `/opt/jerasoft/vcs/portal-backend/config/customer-params.default.json` file as a reference for all available parameters. The table below describes each of them. Please put all settings into your config file and do not change `customer-params.default.json` as it will be overwritten on the system update.

### General Settings

Setting Name	Description	Example
<b>billingUrl</b>	URL of the billing system. As it is accessible from the Client Panel host	"https://127.0.0.1"
<b>companiesId</b>	ID of the <b>Reseller</b> for the Client Panel	3
<b>logFile</b>	Path to the Client Panel log file	" /opt/jerasoft/vcs-data/log/cp.log"
<b>openedEndpoint</b>	URL of the Client Panel (without "/" at the end). This URL will be used to return clients to after processing of the payment by the <b>Payment Gateways</b>	"http://127.0.0.1"
<b>coreApi.url</b>	URL of the Core API service	"http://127.0.0.1:3080"
<b>coreApi.authToken</b>	Authorization token for the Core API service. You can get this token in the <b>System/Users</b> section	"PW2Ln6PSS3vpmmZrCQBV5of2NO7jJbcU"
<b>managementApi.url</b>	URL of the Management API	"https://127.0.0.1/jsonrpc"
<b>managementApi.login</b>	Login of the user used for the integration. You need to have a dedicated user for the integration, use the same user for the Core API service and Management API	"api-client-portal"
<b>managementApi.password</b>	Password of the user used for the integration	"aqGW3loxHag8"

## Output Formatting

The following settings are located under **"defaults"** key of the configuration file.

Setting Name	Description	Example
<b>locale</b>	Default locale to start with. Available settings: en, ru	"en"
<b>perPage</b>	Quantity of rows to display per page. Allowed values: an integer from 1 to 1000	10
<b>roundRates</b>	Quantity of digits after the decimal point for display of rates. Allowed values: an integer from 0 to 16	4
<b>roundAmounts</b>	Quantity of digits after the decimal point for display of amounts. Allowed values: an integer from 0 to 16	2

## Date and Time Formatting

The following settings are located under **"dateTimeConfig"** key of the configuration file. Please refer to [the following guide](#) for a list of possible values.

Date and Time Formatting [section: <b>dateTimeConfig</b> ]		
Setting Name	Description	Example
<b>monthFormat</b>	Format string to display "Month Year" strings	"F Y"
<b>dateFormat</b>	Format string to display dates	"m/d/Y"
<b>dateTimeFormat</b>	Format string to display dates with time	"m/d/Y, h:i A"

## Payment Gateways: PayPal

The following settings are located under **"paymentGateways.paypal"** key of the configuration file. Check your PayPal panel for the required parameters. [Get more details](#).

Setting Name	Description	Example
--------------	-------------	---------

<b>enabled</b>	Defines if the payment gateway is enabled. Allowed values: true, false. Do not forget to enable gateway in the respective section of the billing system	true
<b>sandbox</b>	Defines if the Sandbox mode is enabled. Allowed values: true, false	false
<b>allowCustom</b>	Defines if the custom amount payments are allowed. Allowed values: true, false	true
<b>clientId</b>	PayPal Client ID	test@example.org
<b>clientSecret</b>	PayPal Client Secret Key	
<b>itemName</b>	Item name displayed in the PayPal order	"Credit Your Balance Item"
<b>orderDescription</b>	Order description displayed in the PayPal	"Credit Your Balance"

## Payment Gateways: Authorize.Net

The following settings are located under "**paymentGateways.authorizenet**" key of the configuration file. Check your Authorize.Net panel for the required parameters. [Get more details](#).

Setting Name	Description	Example
<b>enabled</b>	Defines if the payment gateway is enabled. Allowed values: true, false. Do not forget to enable gateway in the respective section of the billing system	true
<b>sandbox</b>	Defines if the Sandbox mode is enabled. Allowed values: true, false	false
<b>allowCustom</b>	Defines if the custom amount payments are allowed. Allowed values: true, false	true
<b>apiLoginId</b>	Authorize.Net API Login ID	
<b>apiTransactionKey</b>	Authorize.Net API Transaction Key	
<b>apiSignatureKey</b>	Authorize.Net API Signature Key	

### Attention

Payment Gateways integration requires proper domain name and real SSL certificate. Please check the [Panel Deployment](#) guideline to get more information.

## Section: Charges History & Payments History

The following settings are located under "**modules.transactionList**" key of the configuration file.

Setting Name	Description	Example
<b>dateRangeDefault</b>	Default dates range in the filter, in days. Allowed values: an integer from 1 to 90	30

## Section: Usage History / Detailed

The following settings are located under "**modules.reportXdrs**" key of the configuration file.

Setting Name	Description	Example
<b>queryOnOpen</b>	Defines if the report should be run right after section open. If set to <b>false</b> , the user will have to hit <b>Query</b> to get the report. Use this option if you have plenty of data to load. Allowed values: true, false	true

<b>dateRangeDefault</b>	Default dates range in the filter, in days. Allowed values: integer 1 to 90	3
<b>additionalColumns</b>	List of additional columns to display. Allowed values: origin, src_party_id	["origin", "src_party_id"]

Section: Usage History / Summary

The following settings are located under "modules.reportSummary" key of the configuration file.

Setting Name	Description	Example
<b>queryOnOpen</b>	Defines if the report should be run right after section open. If set to <i>false</i> , the user will have to hit <i>Query</i> to get the report. Use this option if you have plenty of data to load. Allowed values: true, false	true
<b>dateRangeDefault</b>	Default dates range in the filter, in days. Allowed values: integer 1 to 180	90

Additional Settings

The following settings are located at the top level of the configuration section.

Setting Name	Description	Example
<b>redisMain.hostname</b>	The hostname or IP address to use for connecting to the Redis server.	"localhost"
<b>redisMain.port</b>	The port to use for connecting to the Redis server.	6379
<b>redisMain.database</b>	The Redis database to use.	1
<b>redisCache.hostname</b>	The hostname or IP address to use for connecting to the Redis server.	"localhost"
<b>redisCache.port</b>	The port to use for connecting to the Redis server.	6379
<b>redisCache.database</b>	The Redis database to use.	2

Knowledge Base Articles

Error rendering macro 'contentbylabel'

parameters should not be empty