



# Execution Logs

Execution Logs tab provides information about handlers execution such as date and time of execution, status, duration, etc. The tab is presented in the form of a table with the following columns:




Screenshot: Execution Logs tab

 Provisioning API


Execution Logs




Rows 1 – 3 of 3


| ID  | Date                      | Event |                 | Status  | Name  | Error  | Duration |   |
|-----|---------------------------|-------|-----------------|---------|-------|--|----------|---|
| 153 | 12/20/2016 13:45:15 +0000 | After | Accounts Create | Success | acc 6 |  | 1 ms     |  |
| 156 | 12/20/2016 13:45:18 +0000 | After | Accounts Create | Success | acc 6 |  | 1 ms     |  |
| 179 | 01/10/2017 15:40:07 +0000 | After | Accounts Create | Fail    | acc 6 | Script execution error No such file or directory | 27 ms    |  |

| Column Name | Description                                  |
|-------------|--|
| ID          | Handler's identification number              |
| Date        | Time and date of handler execution           |
| Event       | Details on handler type and event            |
| Status      | Status of a handler: <i>Success/Fail</i>     |
| Name        | Title of the handler                         |
| Error       | Description of the event in case of an error |
| Duration    | Amount of time, spent on handler execution   |

When you click on **Details**  icon, a new window with a description of respective handler execution appears (see screenshot below). This window contains information that JeraSoft Billing sends via the handler.

Click on this icon  to expand logs. For example, logs for handlers with *before* type will only show modified data.

Screenshot: Provisioning details

 **Provisioning API**

acc 6


Event Type: After  
Event: Accounts Create

Status: **Success**  
Date: 12/20/2016 13:45:18 +0000


**DATA**

```
{
  auth_type: "name",
  protocol: null,
  ani: null,
  id_dr_plans: null,
  orig_capacity: null,
  ips: [ ],
  term_tags: [ ],
  term_capacity: null,
  port: null,
  orig_enabled: false,
  id: 178,
  tech_prefix: null,
  term_rate_table: null,
  proxy_mode: null,
  orig_tags: [ ],
  rates_notify_force: false,
  password: null,
  name: "ipre-pre-",
  term_enabled: false,
  notes: "",
  accname: "1",
  voip_hosts: [ ],
  id_clients: 15,
  orig_rate_table: null
}
```

### Advanced Search

By clicking on  red downwards arrow, the following **Advanced Search** drop-down menu is displayed:

Screenshot: Advanced Search drop-down menu



Status:

Event Type: After

Event: Accounts Create

Data:

Error:

Date From:

Date To:

Reset

Search

| Field | Description |
|-------|-------------|
|-------|-------------|

|                            |   |
|----------------------------|---|
| <b>Status</b>              | <p>Indicate handler execution status:</p> <ul style="list-style-type: none"> <li>• <b>Success</b></li> <li>• <b>Fail</b></li> </ul>                                       |
| <b>Event Type</b>          | <p>Select a type of event:</p> <ul style="list-style-type: none"> <li>• <b>After</b></li> <li>• <b>Before</b></li> </ul> <p><b>After</b> event type is set by default</p> |
| <b>Event</b>               | Select from a list of all possible handler events   |
| <b>Data</b>                | Indicate handler execution data, specified in <b>Details</b> pop-up window  |
| <b>Error</b>               | Indicate handler execution data, specified in <b>Error</b> pop-up window  |
| <b>Date From / Date To</b> | Specify first and/or the last date of handler execution   |