

Backup Settings

Backup settings are presented with the following fields:

Screenshot: Backup Settings window

BACKUP SETTINGS

System Backup Period:	<input type="text" value="167"/> hour(s) (0 - do not backup)	How often to backup the system. Please note that actual backup will be done at the time when the Backup Manager process runs.
Destination for Backup Packages:	<input type="text" value="/opt/jerasoft/backups"/>	Absolute path where to put backup packages. It cannot be inside the root of the system.
Include into backup:	<div>Database x</div>	Which components of the system should be included into backup.
Disk usage threshold:	<input type="text" value="40"/> %	Threshold for backup size relative to free disk space. Contact Support Team if you need to change the value.
Leave last X Packages:	<input type="text" value="3"/>	How many last backup packages to leave.
Number of Backup Manager workers:	<input type="text" value="1"/>	Number of threads that run database backup.

Field	Description
System Backup Period	The field value specifies when the system should backup itself (for example, if you enter 24 as a value, it will mean that the system will backup itself every 24 hours).
Destination for Backup Packages	Absolute path to the folder where the system backup copies will be stored . <div><div>Warning</div><div>This folder shouldn't be within any system folder!</div></div>
Include into backup	Specify components of the system which should be included into backup.
Disk usage threshold	The percentage value of the disk space that backup needs free for correct work.
Leave last X Packages	This Parameter specifies how many backup copies will be stored at one given time (for example, if you enter 3 as a value, only three copies will be stored. When the fourth copy is added, the oldest one will be deleted).
Number of Backup Manager workers	Specify the number of system managers that run a database backup .



Attention

The backup will not be created if the disk size is not enough.